

PRODUCT INFORMATION



STARTING FLUIDS THRUST® INSTANT® LIQUID FIRE

CODE
M35-15, M38-15, M39-11
PAGE
1 of 1
DATE
March, 97

FUNCTION AND APPLICATION: To promote quick starting of gasoline and diesel engines under extreme cold conditions.

OUTSTANDING PROPERTIES: Produce quick, smooth starting of gasoline and diesel engines under extreme cold conditions down to -65°F. Saves battery and ignition during cold weather. Contains upper cylinder lubricant and corrosion inhibitors.

USE DIRECTIONS: Spray fluid directly into air cleaner of air intake before starting engine. Avoid spraying for over 5 seconds per attempt. If engine still refuses to start repeat procedure for up to 3 times. If engine still does not start, ignition repairs may be indicated.
ALWAYS AVOID SPRAYING WHILE IGNITION IS ON TO AVOID POSSIBILITY OF EXPLOSION OR FIRE.

PRODUCT LIMITATIONS: Avoid spraying while turning engine simultaneously. Avoid overuse of product when engine fails to start with recommended procedure. Engine damage or personal injury may result. Avoid flooding engine before using. Do not use with engines which use glow plugs (especially diesel passenger autos).

PRECAUTIONS: Contains (CAS#) Diethyl Ether (60-29-7), Aliphatic Petroleum Distillate (142-82-5), Naphthenic petroleum oil (64742-53-6/64742-52-5), and Carbon Dioxide Propellant (124-38-9).

Extremely flammable. Can be explosive when subjected to heat, sparks or open flame. Vapors extremely harmful. Contents under pressure. Eye and skin irritant. Harmful or fatal if swallowed. **FIRST AID:** For inhalation, move to fresh air. If breathing becomes difficult, get prompt medical attention. For eye contact, flush thoroughly with water for 15 minutes while lifting eyelids and get prompt medical attention. For skin contact, wash thoroughly with soap and water. If irritation persists, get prompt medical attention. If swallowed, DO NOT INDUCE VOMITING! Call Poison Control Center, Physician, or Hospital Emergency Room Immediately.

STORAGE & HANDLING: Store in a cool, dry, well ventilated area. Do not puncture or incinerate container. Do not expose to heat, sparks, open flames or temperatures above 120 F. Exposure to high temperatures may cause bursting. Do not place on radiator, stove or in direct sunlight. Keep from contact with electrical connections such as battery terminals. Use with adequate ventilation. Avoid using in low lying or confined areas. Wearing contact lenses while working with this product is inadvisable. Keep away from children and animals.

DISPOSAL: Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

CONTAINER DESCRIPTION: 15 weight ounce and 11 weight ounce aerosols.

Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, NC 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.