

**NEW!**

# ZINC-X

## Corrosion Inhibitor



### The zinc rich, galvanized coating for rust and corrosion protection.

- 95% pure zinc-rich galvanized coating
- Prevents rust and corrosion on all metals
- Up to two years protection
- Works as a paint primer over rust
- Works like a hot-dip on ferrous metals indoors and outdoors
- Fast drying; dries to touch in 10 – 15 minutes
- Withstands water temperature up to 212°F (100°C) and continuous dry heat up to 750°F (400°C)
- Will not yellow, chalk, crack or peel
- Repairs rusted, galvanized and welded surfaces
- Meets or exceeds ASTM A-780 specification
- Does not contain Methyl Ethyl Ketone (MEK)
- Value Performance

### Zinc-X Corrosion Inhibitor is available in this size:

14 oz. (397 grams) aerosol

05616

### General Information

LPS Zinc-X is a zinc rich coating that performs like a hot dip galvanize to prevent rust and corrosion on all types of metals for up to two years. Zinc-X works electro-chemically on all ferrous metals, providing rust and corrosion protection indoors and outdoors. Zinc-X can be used as a primer over rusted metal to repair hot dip galvanizing. Specially formulated Zinc-X provides a tough, flexible coating that will not crack or peel even in extreme heat or cold.

### Properties

<b>Color:</b> Medium-Gray	<b>Specific Gravity:</b> 0.88 – 0.90
<b>Dries to Touch:</b> 10 – 15 minutes	<b>V.O.C. Content:</b> 31% – 33%
<b>Recoat Time:</b> 6 hours	<b>Flash Point:</b> Extremely flammable by CSMA Flame Extension Test
<b>Zinc Content of Dry Film:</b> 88% – 90%	

### Typical applications where Zinc-X Corrosion Inhibitor can be used:

- Acts as a Paint Primer
- Auto and Truck Bodies
- Construction Machinery and Equipment
- Exhaust Stacks, Mufflers and Manifolds
- Farm Machinery
- Fences
- Heating and Air Conditioning Equipment
- Metal Roofs and Gutters
- Offshore Drilling Rigs and Trailers
- Outdoor Furniture and Tools
- Overseas Storage or Shipments
- Pipes and Water Tanks
- Repairs Hot Dip Galvanizing
- Weldments



LPS Laboratories • An Illinois Tool Works Company  
P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 U.S.A.  
TEL: (800) 241-8334 or (770) 934-7800 • FAX: (800) 543-1563 or (770) 493-9206  
Internet Web Site: [www.lpslabs.com](http://www.lpslabs.com)

©2003 LPS Laboratories • LPS® is a registered trademark of Illinois Tool Works • All Rights Reserved • Rev. 10/2003 • Form #X5616

**CERTIFIED  
ISO 9001**  
QUALITY MANAGEMENT SYSTEM