

ELECTRO 140°

CONTACT CLEANER



The high flash point, fast penetrating, non-residue cleaner alternative to CFCs for fine parts.

- **Flash point above 140°F (60°C)**
- **Superior wetting and penetrating action**
- **Controlled evaporation**
- **No residue**
- **Nonconductive**
- **Safe to use on most surfaces**
- **Inverta Spray Valve allows one to spray in an upright or inverted position**

Electro 140° Contact Cleaner is available in these sizes:

| | |
|----------------------------|----------------|
| 11 oz. (312 grams) aerosol | Part No. 00916 |
| 1 gal. (3.78 liters) | 09128 |
| 5 gal. (18.93 liters) | 00905 |
| 55 gal. (208 liters) | 00955 |

Typical applications where Electro 140° Contact Cleaner can be used:

- Coin Counters & Chutes
- Connectors
- Contacts
- Fluid Systems
- Magnetic Tape Heads
- Office Equipment
- Printed Circuits
- Relays and Controls
- Semiconductor Assemblies
- Switches
- Telephone Equipment
- TV Tuners
- Typewriters/Keyboards

General Information

Electro 140° Contact Cleaner is a high flash point cleaner that penetrates, cleans and degreases, without leaving a residue. Electro 140°'s longer cleaning action is especially suited for cleaning electrical and electronic parts as well as other types of delicate mechanisms. Electro 140° does not contain CFCs, 1,1,1 trichloroethane or methylene chloride. Electro 140° has a flash point above 140°F which makes it safe to use in areas where flammability poses a potential problem. Electro 140° is safe to use on most surfaces, but may be harmful to some plastics. Because of its superior wetting action, Electro 140° Contact Cleaner penetrates into minute spaces for thorough and effective cleaning. To enhance drying time, air dry or wipe with an absorbent cloth after applying.

Material Safety Data Sheets are available upon request.

Properties

Flash point:
144°F

% Non-volatiles:
<100 ppm

KB value:
52

Specific gravity:
0.797 @ 77°F

Surface tension:
25.9 dynes/cm @ 77°F

Propellant:
Carbon Dioxide



LPS Laboratories • An Illinois Tool Works Company
P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 U.S.A.
TEL: (800) 241-8334 or (770) 934-7800 • FAX: (800) 543-1563 or (770) 493-9206
Internet Web Site: www.lpslabs.com

LPS® is a registered trademark of LPS Laboratories • ©2001 LPS Laboratories • All Rights Reserved • Rev. 09/2001 • Form #X0916

**CERTIFIED
ISO 9001**
QUALITY MANAGEMENT SYSTEM