

TAPMATIC *Natural* CUTTING FLUID



The high performance, metal cutting fluid designed to lubricate and reaming, tapping or drilling operation.

- Great for steel and aluminum
- Nontoxic and nonhazardous
- Biodegradable
- Does not irritate the skin, eyes or respiratory tract
- Does not contain sulfur, chlorine, chlorinated solvents, water, mineral oil or inactive fillers
- High performance lubricating ability eliminates galling and seizing
- Safe on all metals

Tapmatic Natural Cutting Fluid is available in these sizes:

16 fl. oz. (0.473 liter)	Part No. 44220
1 gallon (3.78 liters)	44230
5 gallons (18.93 liters)	44240
55 gallons (208 liters)	44260

Typical applications where Tapmatic Natural Cutting Fluid can be used:

- Tapping
- Drilling
- Reaming
- Threading
- Facing
- Sawing
- Turning
- Milling
- Broaching
- Engraving
- Boring

General Information

Natural is a biodegradable cutting fluid that does not irritate the skin, eyes or respiratory tract. Its lubricating ability eliminates galling and seizing, and extends tool life. It's recommended for all machining operations including tapping, drilling, reaming, threading, turning, broaching and milling. Natural is safe on all metals. Natural does not contain 1, 1, 1 trichloroethane, CFCs, sulfur, chlorine, chlorinated solvents, water, mineral oil or inactive filler. It is 100% active.

Material safety data sheets are available upon request.

Properties

Appearance:

Clear Green Liquid

Odor:

Citrus Spice

Specific Gravity:

0.888 @ 77°F

Viscosity:

10–15 cps @ 72°F



LPS Laboratories • An Illinois Tool Works Company
P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 U.S.A.
TEL: (800) 241-8334 or (770) 934-7800 • FAX: (800) 543-1563 or (770) 493-9206
Internet Web Site: www.lpslabs.com

LPS® is a registered trademark of LPS Laboratories • ©2001 LPS Laboratories • All Rights Reserved • Rev. 09/2001 • Form #X44204

**CERTIFIED
ISO 9001**
QUALITY MANAGEMENT SYSTEM